

Introducing...

ProSelect™
Treated Wood with Micronized Copper

Vista by Rocky Top

Rocky Top Building Products introduces Vista Railing and Vista Decking - made of ProSelect™ pressure-treated wood

with micronized copper, an environmentally friendly wood preservative.

Surround yourself with timeless beauty with the entire Vista line! Create an outdoor space with superior deck boards and a railing system that exudes style, all at a reasonable price! All Vista products are Kiln Dried After Treatment (KDAT) to help stabilize the lumber and decrease warping and checking.



Secondary Handrail



Provincial



Chicago



Classic



For more information about the Vista line of products, please visit www.rockytopbp.com.

Plus...

Enter to WIN a Jim Shockey Guided Hunt for Canadian Whitetail in Saskatchewan!!

No purchase necessary. See www.rockytopbp.com for official rules and regulations.


JIM SHOCKEY'S
Hunting Adventures

800-274-3443
www.rockytopbp.com



All Vista products are available FSC certified.



The mark of responsible forestry
SW-COC-003540
© 1996 Forest Stewardship Council A.C.

Vista Railing is available in three distinctive profiles and in two sizes, 2" x 4" or 2" x 6". Balusters and post caps are sold separately, and the system is compatible with wood or metal balusters. The distinctive channel inserts can be used interchangeably and can hide fasteners, resulting in a flawless look. To complete the look, secondary handrails are also available.

Each Vista Railing kit includes:

- A 6' or 8' handrail
- Two interchangeable channel inserts

Each secondary handrail kit includes:

- Two secondary handrails, 8' each

Vista Decking is the only choice when looking for a truly superior deck board. This decking has natural beauty and increased strength that surpasses all other decking boards. Only the highest grade Southern Yellow Pine is used to limit knots and other blemishes.

Vista Decking measure 1-3/8" x 5" and is available in 12', 16' and 20' (limited) lengths. Most boards will have the crown or bark side up and two "tension relieving" grooves on the bottom to increase stability.

Vista
Railing
by Rocky Top

Vista
Decking®
by Rocky Top

Building Tips

Keep dry. Vista Railing has been kiln dried after treatment to increase stability, and because it is dry, it will absorb some moisture. To ensure proper fit, keep rail parts dry before assembly.

Paint or stain. Coat all treated rail parts with oil based deck stain, sealant or paint immediately after installation.

Pre-drill. Pre-drill all screw holes to prevent rail parts from splitting.

Use recommended hardware. Use only screws approved for pressure-treated lumber for assembly and installation.

Use wood adhesive. In addition to screws (1-5/8" are best), we recommend using weather-proof wood adhesive between your channel insert and top handrail.

Face channel down. We recommend facing the bottom channel insert down. Facing it up will increase moisture retention and the possibility of decay and fastener failure.

Maintenance Tips

No maintenance is needed to renew resistance to fungi and termites.

To revitalize a dingy appearance caused by dirt, mildew and mold, use a deck brightener to clean the wood.

Check with the experts in the store's coatings department for recommendations on water repellent, stain and cleaner.

Warranty

ProSelect offers a lifetime limited warranty against termites and fungal decay for most residential and agricultural applications. Please see www.proselectwood.com for more details.

Safety Information

This wood has been preserved by pressure-treatment with an EPA-registered pesticide, copper azole, to protect it from termite attack and fungal decay. Wood treated with any preservative should be used only where such protection is necessary or important.

In the treating process, copper azole penetrates deeply into the wood where it remains for many years. However, a small amount of chemical may migrate from preserved wood into surrounding soil over time and may also be dislodged from the wood surface upon contact with skin. Precautions should be taken when handling the preserved wood. Many of these precautions also apply to untreated wood and other building materials.

Handling Precautions:

Dispose of treated wood by ordinary trash collection. TREATED WOOD SHOULD NOT BE BURNED in open fires or in stoves, fireplaces or residential boilers.

When sawing, sanding and machining wood, wear a dust mask. Avoid frequent or prolonged inhalation of sawdust from wood, treated or untreated. Whenever possible, these operations should be performed outdoors.

Wear gloves when working with wood. Wear goggles to protect eyes from flying particles. Use proper techniques when lifting.

Because preservatives or sawdust may accumulate on clothes, they should be laundered before reuse. Wash work clothes separately from other household clothing.