

PRESSURE TREATED FENCING



West Virginia Split Rail

Split Fence

Gates

Warranty

How to Install West Virginia Split Rail Fencing



Rocky Top Building Products

P. O. Box 508

Rocky Mount, VA 24151

800-274-3443

Pressure Treated West Virginia Split Rail



Product Summary

From rustic Appalachia comes a split rail fence like no other, skilled craftsmen draw out the strength and beauty of Appalachian poplar with the same eye to quality as the early settlers of West Virginia. Appalachian poplar is ideally suited to this application. Used for many years in West Virginia Split Rail, the species has proven itself to be an excellent fencing material. Because the species is highly receptive to the treating process it makes an ideal pressure treated split rail post. To increase their strength the posts and poplar rails are pressure treated to ground contact retention in the post and above ground retention in the rail. The pressure treating process forces the preservatives into the wood fibers changing the characteristics of the wood so that it is highly resistant to attack of rot, decay and insects. The treatment leaves no odor or residue, just natural wood grain beauty with a light green hue. This product carries a 30-year warranty from the manufacturer, WVSR.



Specifications

<u>Post Description</u>	<u>Shipping Weight</u>	<u>Average Girth</u>	<u>Approx. Size</u>	<u>Hole Spacing</u>
2 Hole Line	25 lbs.	18"	3" x 6" x 64"	16" on center
2 Hole End & Corner	25 lbs.	16"	4" x 4" x 64"	16" on center
3 Hole Line	35 lbs.	18"	3" x 6" x 84"	16" on center
3 Hole End & Corner	35 lbs.	16"	4" x 4" x 84"	16" on center
<u>Rail Description</u>	<u>Shipping Weight</u>	<u>Average Girth</u>	<u>Approx. Size</u>	
Standard 11' Rail	30 lbs.	12"	Triangular	

Shipping Specifications:

All Line Posts	49 Pcs. per unit
All End Posts	16 Pcs. per unit
All Corner Posts	16 Pcs. per unit
Standard Rails	100 Pcs. per unit

Pressure Treated Gates



Product Summary

These versatile and attractive gates are the perfect match for West Virginia Split Rail fence. Durable and maintenance free, these rustic gates add the finishing touch to any span of fence.

Specifications

Gates are available in either two or three rail style:

<u>Description</u>	<u>Size (Width x Height)</u>	<u>Bundle Size</u>	<u>Shipping Weight</u>
2 Rail Walk Gate	42" x 40"	10	40 lbs. each 400 lbs. / bundle
3 Rail Walk Gate	42" x 48"		

Other sizes available on special order.

THIRTY YEAR LIMITED WARRANTY CERTIFICATE

WVSR, subject to the conditions and limitations listed herein warrants that pressure treated West Virginia Split Rail fence shall be free from natural attrition due to decomposition for thirty (30) years following the date of invoice.

Should any pressure treated West Virginia Split Rail fence be proven to be suffering from said defect covered by this warranty the sole obligation of WVSR, shall be, at its option, to replace free of charge any such product or to reimburse claimant for original purchase price. WVSR shall in no event be liable for the expenses or charges in connection with shipping, installing or otherwise working with the original or replacement material.

WVSR shall have no liability under this warranty for defects caused by abuse, improper installation or improper use; nor does it apply to the natural tendency of some wood to check, warp, twist or discolor.

WVSR reserves the right to discontinue or modify any of its products, including the pressure treated West Virginia Split Rail fence which is the subject of this warranty, and shall under no circumstances be liable as a result of such discontinuance or modification except that WVSR shall not be relieved of the obligation to make a reasonable contribution to the replacement of the post in accordance with the preceding paragraphs.

This warranty shall not cover any claimed defect for which the notice is not received by WVSR, Inc. within ninety (90) days following the discovery or shall it cover any claimed defect with respect to which WVSR be liable for consequential or incidental damages of any kind including damage to persons, property or livestock.

Notices of claim on this warranty must be sent to: Warranty Claims, WVSR, P.O. Box 9, Buckhannon, WV 26201. This warranty is not transferable.

How to Install West Virginia Split Rail Fencing

1. Lay out the corners and ends of the fence and set these posts to correct height, partially back fill for stability.
2. Stretch a string from the ends to line up each post.
3. Dig first line post hole about 10' from starting corner, install this post and rails and repeat until complete.
4. If the distance that the fence covers cannot be worked in multiples of 10', then the distance between the last two posts will be less than rail length and the rails must be cut off. Allow enough length to put a new scarf on the rail by use of a chain saw or hatchet.

NOTE: To compensate for short rails you may want to divide the shortage by reducing the length of rails on both the first and last sections. If this is not required then we recommend that the short section be in a less conspicuous place.

Setting Posts

1. Dig hole 24" to 30" deep, plus 4" extra for a rock or gravel fill for drainage. Exact depth will be dependent on how high you want the first rail above the ground.
2. Put 4" of rock or gravel in posthole, set post, add dirt and compact. Do not finish setting post until next section is installed.
3. Compact the back fill by tamping and sloping it away from the post for drainage.

West Virginia Split Rail proves itself in ease of installation. There is no butting of rails into posts, eliminating exact post setting. The 6" lap on each end of our West Virginia Split Rail will allow for irregularities in post setting without detracting from the overall finished appearance.